

DAO Series

Thermocouple with straining clamp
DAO 5X30JEXT2M

Ref: 2803

Rev: A



DESCRIPTION

Thermocouple type K, J, T, N etc., with relay terminal type end cap, is ideal for fixing using 4.5.6 mm diameter screws. A reinforced version, with armored glass silk cable, can resist a temperature up to 300 °C, with the possibility of adding a miniature compensated connector or standard type K, J, T.

MESUREX is a sensor manufacturer. We can adapt most sensors to your need. Please [contact us](#).

K Green	J Black	T Brown	N Pink	E Purple	R/S Orange	B Grey
---------	---------	---------	--------	----------	------------	--------

TECHNICAL CHARACTERISTICS

Type of thermocouples	K, J, T, N (or others on request)
Precision	Class 1, NF EN 60584-2 standard
Color coding	According to NF EN 60584-3 standard
Dimensions tips	For screws diameter 4.5.6 mm (or other on request)
Cable length	2 meters standard
Temperature use	300°C (other on request)
Connection	Miniature compensated connector (or other on request)
Cable	Armored glass silk K, J, T 0.22mm ² 7x0.2 mm (others on request)

Example: DAO5X30JEXT2M

- J Type
- 2-meter-long cable
- For 5 mm screws



CONTACT

MESUREX

13 Rue des Corroyés

78730 Saint Arnoult en Yvelines (France)

Tel : +33 (0) 1 30 41 23 62

Fax : +33 (0) 1 30 41 23 80

Mail : mesurex@mesurex.fr