

## DC Series

RTD Ref DC19P4

Ref : 4027

Rev : A



### DESCRIPTION

Surface platinum probe PT 100 type, easy to position with its adhesive silicone pad (diameter 18 mm, thickness 4 mm). It is reusable and can measure temperatures from -20 to 65 ° C. It comes with a 2-meter-long extension cable standard (unshielded Teflon, 3-wire mounting).

*MESUREX is a sensor manufacturer. We can adapt most sensors to your needs. Please [contact us](#).*

### TECHNICAL CHARACTERISTICS

Type of PT100	Thin film sensitive element (ships)
Precision	Class A, according to NF EN 60751 standard (+/- 0.15°C to 0°C)
Color coding	According to NF EN 60584-3 standard
Pad dimensions	Silicone washer 18 mm diameter, 4 mm thickness
Cable length	2 meters as standard
Cable Type	Unshielded Teflon 3 conductors, section (0.22mm <sup>2</sup> )
Temperature range	-20/65°C
Connection	On specific request
Option on request	Accuracy of the sensitive element, length of the cable
Fixation	Adhesive washer (can also be non-adhesive)

#### Example: DC19P4

- PT100 surface 19 mm x 4 mm
- 2-meter-long cable, 3-wire-mounting



### CONTACT

#### MESUREX

13 Rue des Corroyés  
78730 Saint Arnoult en Yvelines (France)

Tel : +33 (0) 1 30 41 23 62

Mail : [mesurex@mesurex.fr](mailto:mesurex@mesurex.fr)

Web : [www.mesurex.fr](http://www.mesurex.fr)